

10 11800

PCT/PTO 19 OCT 2004



PCT / IB 0 3 / 0 1 3 5 1

03 APR 2003



INVESTOR IN PEOPLE

REC'D 22 APR 2003

WIPO

PCT


The Patent Office  
 Concept House  
 Cardiff Road  
 Newport  
 South Wales  
 NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 22 January 2003

**PRIORITY DOCUMENT**  
 SUBMITTED OR TRANSMITTED IN  
 COMPLIANCE WITH  
 RULE 17.1(a) OR (b)

An Executive Agency of the Department of Trade and Industry

BEST AVAILABLE COPY

THE PATENT **Patent**  
Office

23 APR 2002

1/77

## Request for grant of a patent

*(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)*The Patent Office  
Cardiff Road  
Newport  
Gwent NP10 8QQ

1. Your reference

PHGB020049

23APR02 E713220-1 D02879

P01/7700 0.00-0209219.5

2. Patent application number

*(The Patent Office will fill in this part)*

0209219.5

Full name, address and postcode of the or of  
each applicant (*underline all surnames*)KONINKLIJKE PHILIPS ELECTRONICS N.V.  
GROENEWOUDSEWEG 1  
5621 BA EINDHOVEN  
THE NETHERLANDSPatents ADP Number (*if you know it*)If the applicant is a corporate body, give the  
country/state of its incorporation

THE NETHERLANDS

7419296001

Title of the invention

ELECTRONIC DEVICE INCLUDING A DISPLAY

Name of your agent (*if you have one*)"Address for service" in the United Kingdom  
to which all correspondence should be sent  
(*including the postcode*)BRIAN T STEVENS  
Philips Intellectual Property and Standards  
Cross Oak Lane  
Redhill  
Surrey RH1 5HAPatents ADP number (*if you know it*)

7137623001

If you are declaring priority from one or more  
earlier patent applications, give the country  
and the date of filing of the or of each of these  
earlier applications and (*if you know it*) the or  
each application number

Country

Priority Application number  
(*if you know it*)Date of filing  
(*day/month/year*)If this application is divided or otherwise  
derived from an earlier UK application, give  
the number and the filing date of the earlier  
application

Number of earlier application

Date of filing  
(*day/month/year*)Is a statement of inventorship and of right to  
grant of a patent required in support of this  
request? (*Answer "Yes" if:*

YES

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document.

Continuation sheets of this form

Description

Claims(s)

Abstract

Drawings

5 ✓

2 ✓

1 ✓

2

ONE

SW

10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents

Statement of inventorship and right  
to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and  
search (*Patents Form 9/77*)


Request for substantive examination  
(*Patents Form 10/77*)

Any other documents  
(*Please specify*)

I/We request the grant of a patent on the basis of this application.

11.

Signature



Date 22-04-2002

12. Name and daytime telephone number of  
person to contact in the United Kingdom

01293 815294

(Brian Stevens)

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered "Yes" Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.

## DESCRIPTION

## ELECTRONIC DEVICE INCLUDING A DISPLAY

5        This invention relates to electronic devices including a display, particularly but not exclusively portable devices.

      Devices frequently termed "web pads" or multimedia tablets" are becoming popular, which comprise a hand held portable device with a display  
10    output and some form of input interface. The display screen typically has a touch sensitive input, which may be the main user input to the device, although other inputs may be provided such as some keys and a joystick. These devices are used for web browsing or viewing video material, or indeed combinations of these.

15        These devices are typically relatively small, for example at most A4 size, and are hand held. It has been proposed to enable the display to be driven either in a landscape or a portrait mode, and the physical orientation of the device is simply adapted to the desired mode.

      It is increasingly common to use split screen configurations to view  
20    different information sources simultaneously, for example video data, web data or teletext information. A problem with the partition of a screen to display multiple data sources is that the aspect ratio for video data, at least, should be kept constant. If a video output is reduced in size to provide space for the display of other data, the partitioning of the screen results in an irregular shape  
25    for the other data. As a result, some display area is either wasted, or else the aspect ratio of the video data is altered which distorts the video image.

      According to the invention, there is provided an electronic device including an electronic display comprising a screen and circuitry for providing  
30    display data to the screen, wherein the circuitry is operable in at least two modes, a first mode in which display data is provided to the screen for viewing in a first orientation and a second mode in which display data is provided to

the screen for viewing in a second, orthogonal, orientation, and wherein in the first mode the display data comprises a first image for display substantially filling the screen, and in the second mode the display data comprises second and third images for occupying different areas of the screen.

5 This device enables a single image to fill the screen in one orientation, and if two (or more) images are to be viewed simultaneously, a perpendicular orientation can be used. This enables the aspect ratio for at least one of the second and third images to be the same as for the first image, whilst still filling the width of the screen. Thus, the second and third images may each occupy  
10 a rectangle, with one rectangle having the same aspect ratio as the screen, and with the second and third rectangles together substantially filling the screen.

The screen may have an aspect ratio of 16:9, for standard video data. In the first mode, a video image will fill the screen. In the second mode, the  
15 video image is reduced to 9/16 of its linear dimensions, and the resulting image then fills the width of the screen (which is the shorter side in the second orientation).

Alternatively, the screen may have an aspect ratio of approximately  $\sqrt{2}:1$ . In this case, the rotation of the screen can result in two sub-screens of  
20 identical aspect ratio.

The second and third images are preferably provided one above the other and occupy substantially the full width of the screen in the second orientation.

The display screen may be rotatable with respect to the device between  
25 the first and second orientations. This enables the orientation of other input devices, such as keys, to be kept constant. This will be appropriate if the device includes a keyboard. However, this may not be required, and it may be appropriate simply to rotate the entire device, for example if the main input is a touch-sensitive screen.

30 The input devices may be detachable from the part of the device carrying the screen, for example a remote joystick, keyboard, mouse etc.

The invention also provides a method of displaying data on a screen comprising:

determining whether to display according to a first or second mode of operation;

5       when displaying in the first mode of operation, providing display data comprising an image to substantially fill the screen in a first orientation, and

      when displaying in the second mode of operation, providing display data comprising second and third images for occupying different areas of the screen in a second, orthogonal, orientation.

10       The step of determining whether to display according to a first or second mode of operation may be carried out automatically in dependence on the display data, or in response to an instruction from a user of the device.

      Examples of the invention will now be described in detail with reference  
15 to the accompanying drawings, in which:

      Figure 1 shows a device according to the invention;

      Figure 2 shows the two screen orientations of the device of Figure 1, for a first screen aspect ratio;

      Figure 3 shows the two screen orientations of the device of Figure 1, for  
20 a second screen aspect ratio; and

      Figure 4 shows a second example of device according to the invention.

      Figure 1 shows an electronic device 10 of the invention. The device is a portable device, for example for viewing web and video data. The device 10  
25 includes a display 12, for example a liquid crystal display, having a screen 14. Internally, conventional circuitry is provided for driving the display.

      The screen 14 has a touch sensitive input surface, and this may avoid the need for other manual input interfaces, although by way of example, some key inputs 16 and a remote joystick 18 are shown. There are many other  
30 possible input devices, such as a mouse pad for moving a cursor around the screen and a numeric or even a full keyboard.

In accordance with the invention, the display can be driven in at least two modes, a first mode in which display data is provided to the screen for viewing in a first orientation and a second mode in which display data is provided to the screen for viewing in a second, orthogonal, orientation. In particular, in the first mode a first image for display substantially fills the screen, whereas in the second mode, two separate images occupy different areas of the screen.

Figure 2 shows the display in the two orthogonal orientations when the screen has an aspect ratio of 16:9, which makes the screen suitable for widescreen video format.

In the normal landscape orientation, a video image can fill the screen as shown in Figure 2A. In the second portrait orientation shown in Figure 2B, two images are viewed simultaneously. The aspect ratio for the top of the two images in Figure 2B is the same (i.e. 16:9), with linear dimensions reduced to 9/16, and the image fills the width of the screen. This leaves a rectangle for the image below, which may for example be used for web browser data associated with the video (or live TV) broadcast. As shown in Figure 2B, the aspect ratio for the remaining portion of the screen is 9:10.9375.

As shown in Figure 3, the screen may have an aspect ratio of  $\sqrt{2}:1$ . In this case, the rotation of the screen can result in two sub-screens of identical aspect ratio (because  $\sqrt{2}:1 = 1:\sqrt{2}/2$ ). This aspect ratio also enables four sub-screens of identical aspect ratio to fill the screen in the landscape orientation.

Typically, the complete device will be rotated to enable viewing in the selected orientation. The input devices may be detachable from the part of the device carrying the screen, for example a remote joystick, keyboard, mouse etc, so that they can maintain their required orientation when the screen part of the device is rotated.

Alternatively, and as shown in Figure 4, the display screen may be rotatable with respect to the device between the first and second orientations, as shown by arrow 20. This enables the orientation of other input devices, such as keys, to be kept constant. This may be appropriate, for example, if the device includes an integrated keyboard.

In order to switch between display modes, the user may make an appropriate input. Alternatively, this may be automatic in dependence on the display data. If the display is physically rotatable (as in Figure 4), the orientation can be sensed, and the display driven appropriately.

The ability to drive the display in two modes will require adaptation to the operation of a conventional display. Preferably, the adaptation is purely in software, so that no adaptation of the row and column driver circuits is required. Devices are known with the ability to drive the display in landscape or portrait mode, and the specific implementation of the invention will be routine to those skilled in the art.

Other modifications will be apparent to those skilled in the art.



## CLAIMS

1. An electronic device including an electronic display comprising a screen and circuitry for providing display data to the screen, wherein the circuitry is operable in at least two modes, a first mode in which display data is provided to the screen for viewing in a first orientation and a second mode in which display data is provided to the screen for viewing in a second, orthogonal, orientation, and wherein in the first mode the display data comprises a first image for display substantially filling the screen, and in the second mode the display data comprises second and third images for occupying different areas of the screen.
2. A device as claimed in claim 1, wherein the screen has an aspect ratio of approximately 16:9.
3. A device as claimed in claim 1, wherein the screen has an aspect ratio of approximately 1.4:1.
4. A device as claimed in any preceding claim, wherein the second and third images are provided one above the other and occupy substantially the full width of the screen in the second orientation.
5. A device as claimed in any preceding claim, wherein the display screen is rotatable with respect to the device between the first and second orientations.
6. A method of displaying data on a screen comprising:  
determining whether to display according to a first or second mode of operation;  
when displaying in the first mode of operation, providing display data comprising an image to substantially fill the screen in a first orientation, and  
when displaying in the second mode of operation, providing display

data comprising second and third images for occupying different areas of the screen in a second, orthogonal, orientation.

7. A method as claimed in claim 6, wherein the second and third  
5 images are provided one above the other and occupy substantially the full width of the screen in the second orientation.

8. A method as claimed in claim 6 or 7, wherein the step of  
determining whether to display according to a first or second mode of  
10 operation is carried out automatically in dependence on the display data.

9. A method as claimed in claim 6 or 7, wherein the step of  
determining whether to display according to a first or second mode of  
operation comprises receiving an instruction from a user of the device.

15

## ABSTRACT

## ELECTRONIC DEVICE INCLUDING A DISPLAY

5        A device with a display is operable in at least two modes, a first mode in  
which display data is provided to the screen for viewing in a first orientation  
and a second mode in which display data is provided to the screen for viewing  
in a second, orthogonal, orientation. In the first mode, the display data fills the  
screen, and in the second mode the display data comprises two images for  
10    filling the screen. The aspect ratio for at least one of the two images in the  
second mode can then be the same as for the image in the first mode.

[Fig 3]

1/2




FIG. 1




FIG. 2




FIG. 3

PHGB020049




FIG. 4

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**